

BrickCloak Window Head - nominal 10mm backing panel with nominal 18mm brick slip corners affixed by approved adhesive

Continuous bead of mastic sealant to be applied between edge of BrickCloak panel and window frame to create a weather tight seal

BrickCloak Left Hand Window Jamb - nominal 10mm backing panel with nominal 18mm brick slip corners affixed by approved adhesive

Continuous bead of mastic sealant to be applied between edge of BrickCloak panel and window frame to create a weather tight seal

76 mm

102 mm

ICF System - rigid XPS

ICF System - concrete core

ICF System - rigid XPS

Window



REV	Description	Date	Author

Revision History

Title:		Drawing Number:	
BrickCloak Installation - Window Head		BBSL00014	
Sheet:	Of	Rev	
1	1	1	



Notes:

Fitting instructions shown are to be undertaken prior to the application of pointing mortar  
 Mastic sealant to be fully cured prior to the application of pointing mortar - allow 24hours  
 BrickCloak panels fastened to ICF substrate via timber battens fastened to furring bars of ICF, or fastened directly into concrete of ICF substrate. See ICF fixing drawings for detail.

Drawn:

PE

Scale:

Date:

15/7/16

Approved:

Title:

BrickCloak Installation - Window Head

Drawing Number:

BBSL00014

Sheet:

1

Of

1

Rev

1