



Brick Slip Tracking System



Image shows 1200mm x 2400mm tracking sheet bonded to a 25mm XPS insulation backing panel.

Quick and easy brick slip assembly for:

- External Wall Insulation (EWI)
- Refurbishments
- Cladding
- Modular buildings
- Leisure and park homes
- Retail display walls
- Domestic feature walls

Adopts horizontal tracking guides to ease brick slip installation

Available as separate sheets or pre-bonded to specified backing panels:

- XPS (0.033W/mK) 17.5mm to 50mm
- EPS and EPS Plustherm (Grey 0.03W/mk) up to 250mm thick
- Cement particle Board
- Other backing materials available on request

Tracking sheet brick size options:

- Metric – supports brick heights up to 68mm
- Imperial – supports brick heights up to 75mm

Supports brick slip thickness 15mm to 22mm

Available sizes:

- 1200mm x 2400mm (Metric/Imperial)
- 1200mm x 1200mm (Metric/Imperial)
- 1200mm x 800mm (Imperial)
- 1200mm x 750mm (Metric)
- 1200mm x 600mm (Metric)

Standard tracking sheet material – 1mm thick recycled HIPS (flame retardant ABS available as option)

15mm vertical boarders to facilitate sealing of panel joints with a suitable waterproof tape.

Fixing methods dependent upon backing substrate, 36 fixing points per 1200mm x 2400mm panel required

Brick Slips to be applied to tracking panel using supplier recommended adhesive only



Brick Bond Solutions Limited

Unit 6 Healey New Mills
Healey Road
Ossett
West Yorkshire
WF5 8NF

07825 304998

www.brickbondsolutions.com

sales@brickbondsolutions.co.uk